



# Introducing the LogLogic® LG400

## Centralized Windows Event Log Collection for the Enterprise

The LogLogic LG400 is a gateway collection appliance designed to leverage the capabilities of LogLogic's Project Lasso software. Using the LG400 gateway appliance, enterprise customers can centralize their Windows Event log collection, eliminating the need to manage individual agents on monitored Windows devices, greatly reducing maintenance costs and the impact on monitored servers in terms of storage and processing. The LG400 solution enables customers to monitor hundreds of remote Windows machines from a single location, converting collected Windows Event logs into a syslog-ng message stream that can then be collected and processed by LogLogic the LX, ST, or MX family of appliances. The LG400 greatly simplifies the capture of standard, application-specific, and custom Windows Events across the network.

### Product Specifications

#### Lasso Application

- Supports up to 500 remote Windows log sources and up to 2500 messages per second\*
- Converts remote Windows Events into a syslog-ng message stream

#### System Management

- Command Line Interface
- Web-based GUI for appliance administration
- SNMP Support

#### Device Support

- Windows Event log collection from Windows 2000 and 2003 servers, and Windows 2000 and XP Professional workstations
- Able to monitor Windows System, Security, Application, DNS Server, AD Server, File Replication Service logs, and custom logs

#### Safety Certification

- Safety: FCC Class A, CE, UL Listed
- Radiated Emissions

Test Method	Frequency Range	Result
CISPR 22	30 to 1000 MHz	Pass
EN 55022	30 to 1000 MHz	Pass
FCC Part 15	30 MHz to 16 GHz	Pass
ICES-003	30 to 1000 MHz	Pass
V-3/2006.04	30 to 1000 MHz	Pass

### Features and Benefits

- **Centralized Windows Event log collection, eliminates the need for countless Windows collection agents on each server**
- **Appliance-based gateway solution, greatly simplifies deployment and management costs**
- **An integral component of a full log management solution when used with other LogLogic appliances**

### Hardware Specifications

Chassis: 1U, 19" rack-mountable

Memory: 4 GB

Raw Storage: 500 GB mirrored

Hard Drives: Hot swappable

Power Supplies: 100/240 AC power

CPU: Quad Processor

Ethernet: 2x 10/100/1000

Max Power Consumption: 300 Watts

### More Information

Visit [www.loglogic.com](http://www.loglogic.com) or contact a LogLogic representative by email: [info@loglogic.com](mailto:info@loglogic.com), or phone: 1.888.347.3883

\*Performance may vary, depending on the following factors, including:

- Number of hosts and workstations being monitored
- Total number of events generated by all hosts and per host on average
- Maximum number of events generate by a single host
- Number and size of event logs being monitored
- Available host platform resource (e.g. available RAM, CPU utilization)
- Effective network bandwidth

LogLogic is a registered trademark in the USA and/or other countries. All other brand names, product names, or trademarks belong to their respective holders. LogLogic reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

© 2009 LogLogic, Inc. All rights reserved.